



## Technical Data Sheet



G25 (L)  
single acting, single air drive head  
(Standard= Bottom inlet)

G25 (L)

» Oil service

G25 (L) VE

» Water service

### Technical Data:

|                                    |                             |
|------------------------------------|-----------------------------|
| Air drive pressure:                | 1 - 10 bar / 14.5 - 145 psi |
| Calculated working pressure:       | 280 bar / 4060 psi          |
| Pressure ratio:                    | 1:28                        |
| Displacement volume/double stroke: | 35.3 cm³ / 2.15 cu.inch     |

### Connections:

|                                |                                 |
|--------------------------------|---------------------------------|
| Inlet:                         | Standard: Bottom Inlet 3/4" BSP |
| Outlet:                        | 3/4" BSP                        |
| Air drive:                     | 3/4" BSP                        |
| Maximum operating temperature: | 60°C                            |
| Net weight:                    | 14.5 kg                         |

Pressure and flow performances, please see enclosed graph.

### Wetted materials of construction:

|               |                                                    |
|---------------|----------------------------------------------------|
| Seal package: | G25(L): Polyurethane, NBR<br>G25(L)VE: UHMWPE, FKM |
| Pump Body:    | 1.4404                                             |
| Piston:       | 1.4542                                             |
| Fittings:     | G25(L): 1.4305<br>G25(L)VE: 1.4404                 |

### Approximate Dimensions:

|    |          |
|----|----------|
| A: | 309.5 mm |
| B: | 181 mm   |
| C: | 272 mm   |

### Available Options:

|                                           |                            |
|-------------------------------------------|----------------------------|
| Seal material for oil service:            | G25 (L)                    |
| Seal material for water service:          | G25(L)VE                   |
| Side inlet:                               | G25(L)S/ G25(L)VES         |
| Special inlet and outlet ports, i.e. NPT: | G25(L)-NPT<br>G25(L)VE-NPT |

Special seal material to handle special fluids on request.

### Available Accessories:

|                                                                                                                                                                     |                                                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|
| Air control units with filter pressure regulator, control pressure gauge and shut off valve:                                                                        | G25(L) with C2                                                            |
| To protect the pump against excessive outlet pressures or to limit the outlet pressure, a safety valve can be fitted to the air control unit in the air drive line. | G25(L) with C2/SV-air (The required outlet pressure has to be indicated.) |

Please consult factory for more information. All technical and dimensional information subject to change. All General Terms and Conditions of sale, including limitations of our liability, apply to all products and services sold.

## Leistungsdigramm/Performance Graph G(SF) 25

