



Technical Data Sheet



G60 (L)
single acting, single air drive head
(Standard= Bottom inlet)

G60 (L)

» Oil service

G60 (L) VE

» Water service

Technical Data:

Air drive pressure:	1 - 10 bar / 14.5 - 145 psi
Calculated working pressure:	630 bar / 9135 psi
Pressure ratio:	1:63
Displacement volume/double stroke:	15.4 cm³ / 0.94 cu.inch

Connections:

Inlet:	Standard: Bottom Inlet 3/4" BSP
Outlet:	1/2" BSP
Air drive:	3/4" BSP
Maximum operating temperature:	60°C
Net weight:	13.5 kg

Pressure and flow performances, please see enclosed graph.

Wetted materials of construction:

Seal package:	G60(L): Polyurethane, NBR G60(L)VE: UHMWPE, FKM
---------------	--

Pump Body:	1.4313
------------	--------

Piston:	1.4542
---------	--------

Fittings:	1.4542
-----------	--------

Approximate Dimensions:

A:	325 mm
----	--------

B:	181 mm
----	--------

C:	272 mm
----	--------

Available Options:

Seal material for oil service:	G60 (L)
Seal material for water service:	G60(L)VE
Side inlet:	G60(L)S/ G60(L)VES
Special inlet and outlet ports, i.e. NPT:	G60(L)-NPT G60(L)VE-NPT

Special seal material to handle special fluids on request.

Available Accessories:

Air control units with filter pressure regulator, control pressure gauge and shut off valve:	G60(L) with C2
--	----------------

To protect the pump against excessive outlet pressures or to limit the outlet pressure, a safety valve can be fitted to the air control unit in the air drive line.	G60(L) with C2/SV-air (The required outlet pressure has to be indicated.)
---	---

Please consult factory for more information. All technical and dimensional information subject to change. All General Terms and Conditions of sale, including limitations of our liability, apply to all products and services sold.

