



Technical Data Sheet

GSF35 (L)

» Special liquids



GSF35 (L)

single acting, single air drive head
with distance piece (Standard= Bottom inlet)

Technical Data:

Air drive pressure: 1 - 10 bar / 14.5 - 145 psi

Calculated working pressure 400 bar / 5800 psi

Pressure ratio: 1:40

Displacement volume/double stroke: 24.5 cm³ / 1.49 cu.inch

Connections:

Inlet: Standard: Bottom Inlet 3/4" BSP

Outlet: 3/4" BSP

Air drive: 3/4" BSP

Maximum operating temperature: 60°C

Net weight: 19.0 kg

Pressure and flow performances, please see enclosed graph.

Wetted materials of construction:

Seal package: GSF35(L): PTFE
GSF35(L)VE: UHMWPE, FKM

Pump Body: 1.4404

Piston: 1.4542

Fittings: 1.4404

Approximate Dimensions:

A: 409.5 mm

B: 181 mm

C: 272 mm

Available Options:

Side inlet: GSF35(L)S

Special inlet and outlet ports, i.e. NPT: GSF35(L)-NPT

Special seal material to handle special fluids on request.

Available Accessories:

Air control units with filter pressure regulator, control pressure gauge and shut off valve: GSF35(L) with C2

To protect the pump against excessive outlet pressures or to limit the outlet pressure, a safety valve can be fitted to the air control unit in the air drive line. GSF35(L) with C2/SV-air (The required outlet pressure has to be indicated.)

Please consult factory for more information. All technical and dimensional information subject to change. All General Terms and Conditions of sale, including limitations of our liability, apply to all products and services sold.

Leistungsdigramm/Performance Graph G(SF) 35

Prüfflüssigkeit/Test Liquid: Wasser-Öl-Emulsion/Water Oil Emulsion ca. 1 - 10 cst

